


NOTES:

1. REMOVE JUMPER JA TO PREVENT HANDSWITCH INITIATED MOTION

TERMINAL BLOCK CONFIGURATION JUMPERS:
 JUMPERS J1 AND J2 ARE REQUIRED, J3 IS OPTIONAL

	J1	J2	J3
* <input type="checkbox"/> STANDARD (CW INCR SIG)	D-M	F-N	
<input type="checkbox"/> STANDARD (CCW INCR SIG)	D-N	F-M	
<input type="checkbox"/> REVLOS			E-F
<input type="checkbox"/> FWDLOS			E-D



17-5507-10o A

SIZE:
A

THIS DOCUMENT IS A COPY AND IS NOT THE SOURCE DOCUMENT. INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTICE. THE INFORMATION CONTAINED HEREIN IS COPYRIGHTED BY HAROLD BECK AND SONS, INC. CHANGES TO THE DOCUMENT ARE PROHIBITED. CONTACT A BECK SALES ENGINEER IF A CERTIFIED DRAWING IS REQUIRED.

HAROLD BECK & SONS INC

NEWTOWN INDUSTRIAL COMMONS NEWTOWN, PENNSYLVANIA 18940 USA

TITLE:
WIRING DIAGRAM GROUP 11-1X7/2X7/3X7/407/417/467
240 VOLT 0 AUX SWITCHES 1 POTENTIOMETER
CW/CCW

DRAWN: CHH 10-12-07	SCALE: NONE	DRAWING NO: 17-5507-10o	REV: A
CHECKED: GMD 10/15/07		SHEET NO. 1 OF 1	
APPROVED: JHM 10/16/07			